

SOLUTION HIGHLIGHTS

Sigma: The next generation of instant card issuance

Entrust Sigma Financial Card Card Printers are specifically designed for today's cloud environments and give you the ability to easily issue the most secure financial cards in the world.

- **Simple:** From unboxing to issuing cards to managing your printer, we made sure Sigma was the most user-friendly card issuance solution in the world
- **Secure:** Our industry-leading issuance security architecture will keep your cards and your customers' data safe and secure each step of the issuance process
- Smart: Forward-thinking technology and scalability allow you to expand your card issuance program as your needs evolve



KEY FEATURES & BENEFITS

The world's most user-friendly financial card printer

- Intuitive printer dashboard lets you see printer status, order supplies, check cleaning status, update firmware, or contact help – all from your mobile device
- Seamless self-service lets you access how-to videos and other helpful resources by simply scanning a QR code on the LCD display
- Variable LED light ring lets you incorporate brand colors or other customization into your ambient environment
- Pre-loaded ribbon cassettes make switching ribbons easy
- Optional multi-hopper enables multiple card designs from a single printer
- Removable card cassettes make securing cardstock overnight a breeze





Unmatched security

- Dual-control access with security locks protects card stock, supplies, and rejected cards, meeting Visa and Mastercard security requirements
- Card stock is easily removable for secure overnight storage
- Secure boot protects system from malware or virus on boot-up
- Trusted Platform Module (TPM) manages the printer's own TLS/SSL certificates and keys
- Connection and data sent between DATACARD® Adaptive Issuance software and printer is encrypted
- Customer data is encrypted and is not stored in the printer after printing is complete
- Our cloud-hosted instant issuance solutions are the only ones in the industry that are PCI-CP-certified

Flexible, scalable, and easily integrated into your IT environment

- Issuance capabilities include:
 - Full-color or monochrome direct tocard printing
 - Magnetic stripe encoding
 - Contact or contactless smart card encoding
- Choose on-premises or cloud-hosted deployment
- Easily expand your issuance program as your needs change:
 - Add multi-hopper for multiple pre-designed card feeding
 - Add embosser unit with metallic tipping foil to produce elegant-looking cards
- A full suite of services is available to help ensure your instant issuance program runs smoothly at every one of your branches





TECHNICAL SPECIFICATIONS

Standard Features & Supplies

Print technology	Dye sublimation / resin thermal transfer	
Print capabilities	Single- or dual-sided edge-to-edge, full-color, and monochrome printing	
Print resolution	 Standard mode: 300 dots per inch (dpi) (300 X 600, 300 X 1200) standard text, bar code, and graphics printing 	
	 Datacard® TrueMatch™ printing technology. Ability to conform to ICC color workflow 	
Print speed	Single-sided color ribbon (YMCKT): up to 250 cards per hour (cph) Double-sided color ribbon (YMCKT-KT): up to 180 cards per hour (cph) Double-sided monochrome ribbon (black HQ): up to 500 cards per hour (cph)	
Card capacity	Input hopper: 125 cards (based on 0.03-in. card thickness) Output hopper: 25 cards Reject holding tray: 10 cards Front exception card slot	
Card sizes	Thickness: 0.010 inches to 0.040 inches (0.25mm - 1.016mm) Dimension: ID-1, CR-79	
Operating environment	Temperature: 60°F to 95°F (15°C to 35°C) Humidity: 20-80% RH - non condensing	
Magnetic stripe encoding	ISO 7811 three-track support (high- and low-coercivity) JIS Type II single-track option	
Smart card encoding	 Single wire connectivity; supports production of EMV level-1 compliant cards Contact smart card encoding: ISO 7816 T=0 (T=1), Class A 5V (3V and 1.8V) Contactless smart card encoding: ISO 14443 - A & B, ISO 15693, MiFare Series, DESFire Series EV1/EV2, HID iCLASS Series, HID Prox (125 KHZ) 	
Security features	 Software-activated lock to secure card stock, supplies, and reject card hopper TLS/SSL encryption, supports AES-256 Bolt-down ready Secure cable lock (sold separately) Concealed output hopper Password-protected cabinet Non-resettable card counter for auditing 	
LCD display languages	English, Spanish, German, Italian, and Japanese	
Physical dimensions	Printer: L 17.4 in x W 8.9 in x H 9.0 in $/$ 44.2 cm x 22.6 cm x 22.9 cm Printer with optional multi-hopper: 23 in x 13.4 in x 16.2 in (58.4 cm x 34 cm x 41.1 cm)	
Weight	Printer: 12.1 lbs (5.49 kg) Printer with multi-hopper: 30.9 lbs (14.02 kg)	
Connectivity	USB, Ethernet, and WiFi • WiFi types: 802.11g/n • Authentication modes: None, WPA2 • Dual-band 2.4GHz & 5GHz	
Driver operating system support	 Windows 10 version 1909 - 64-bit - enterprise, home, professional Windows 10 - 32 bit - professional or enterprise 	
Warranties	36 months	



Optional Features & Supplies

Multi-hopper	Six-compartmen	t hopper, 125-card capacity each (750 cards total)
Color ribbons	YMCKT	500 images
	YMCKT-KT	350 images
	KTT	750 images
	YMCKL-KT	300 images
	ST-KT	500 images
	GT-KT	500 images
Monochrome ribbons	Black, blue, red, green, silver matte, gold matte, silvermetallic, and gold metallic: 1500 images	

Color ribbon guide: Y=Yellow, M=Magenta, C=Cyan, K=Black, T=Topcoat, S=Silver matte, G=Gold matte



Single-hopper















U.S. Toll-Free Phone: 888 690 2424 International Phone: +1 952 933 1223 info@entrust.com